

EVALUATION KITS



EVALUATION KITS

Laboratory Kits for Microwave Generators

To speed up the evaluation of the highly innovative LEANFA technology, characterized by an optimal combination of solid-state microwave generators and advanced software algorithms, we have conceived two **Evaluation Kits**, ready for a true plug-and-play experience.

The **STARTER Evaluation Kit** is built around **one** 2450MHz 250W OEM generator, and it comes with a USB interface card, a forced-air cooling system, an AC/DC switching power supply and with the *LeanOn* Control and Monitoring application for Windows OS. It is the basic kit to learn the advantages of our solid-state generators in terms of parametric accuracy, real-time interaction with the processed material and extreme operating flexibility, featuring CW and pulsed radiation modes.

The **PHASESHIFTER Evaluation Kit** is built around *two to four* 2450MHz 250W OEM amplifiers, and it comes with a USB interface card, a forced-air cooling system and an AC/DC switching power supply for each included amplifier and an *advanced synthesizer* with multiple outputs capable of accurate frequency synchronization and 360° independent phase rotation. The hardware kit is accompanied by the *LeanOn* Control and Monitoring application for Windows OS.

The software comes with real-time diagrams and produces complete data reports. Optionally, the *LeanOn* application can be provided with a smart *Recipe Editor*, very useful to test the **KOPERNICOOK**® concept, allowing advanced thermal profile engineering without using stirrers or turntables.



QUICK OVERVIEW

Evaluation Kits featuring 1 to 4 OEM solid-state modules

"STARTER" Evaluation Kit for basic technology assessment

"PHASESHIFTER" Evaluation Kit for advanced R&D experimentation

80-275 Vac universal power supply

2400-2500MHz frequency range

Real-time measurement of reflected power

LeanOn PC software platform for advanced Monitoring & Control

CW and pulsed radiation modes

Provided with forced-air cooling

Fully isolated RF output stages

Optional Frequency Scan for STARTER kit

Optional Recipe Editor for PHASESHIFTER kit



EVALUATION KITS

Laboratory Kits for Microwave Generators

Technical Specifications

It۵	me	inc	lud	hal

SW Option

Operating Frequency

Radiation Modes

Items included

Operating Frequency

Phase Shift

Radiation Modes

Software Option

"STARTER" EVALUATION KIT

1 pc. 2450MHz 250W OEM generator with N output

1 pc. forced-air cooling system

1 pc. USB interface card

1 pc. AC/DC 600W power supply

LeanOn Control and Monitoring application for Windows OS

Frequency scan for reflected power minimization

2400-2500MHz step 2MHz

CW and Pulsed

"PHASESHIFTER" EVALUATION KIT

2 to 4 pcs. 2450MHz 250W OEM amplifiers with N output

2 to 4 pcs. forced-air cooling systems

1 pc. USB interface card

2 to 4 pcs. AC/DC 600W power supplies

1 pc. advanced synthesizer with 2 to 4 outputs

LeanOn Control and Monitoring application for Windows OS

2400-2500MHz step 100kHz, all modules synchronized

0° to 360° step 1.4°

CW and Pulsed

Recipe Editor for LeanOn platform

NOTE: Both items are conceived as evaluation equipment for laboratory experimentation, they are not suited for 24h continuous prolonged operation. Real industrial use requires specific cooling solutions, to be tailored around each specific process.







"PHASESHIFTER" Evaluation Kit

